


TECHNICAL DATASHEET

LENA-RX 6W

01-07-2020



VT/LENA-RX/6W/4000K/SMD/ $\text{Ø}105$ /CB/LED PANEL/REC

NOTES

General Informations

| | |
|-------------------------|------------------|
| Stock Code | 2023920 |
| HSC/GTIP Code | 9405.10.98.50.00 |
| EAN-13 (Inbox Barcode) | 6970233836032 |
| ITF-14 (Outbox Barcode) | 26970233836036 |

Lighting Characteristics

| | |
|-----------------------|--------------|
| Luminous Flux | 570 lumen |
| Time for 60% of Lumen | <0.5 seconds |
| Light Beam Angle | 120° |
| Flicker | No |
| LED Type | SMD 2835 |

Electrical Characteristics

| | |
|-----------------------------|---------------|
| Current Type | AC |
| Operation Voltage | 180-240 Volt |
| Operation Frequency | 50/60 Hertz |
| Electrical Current | 0,027 Amper |
| Power | 6 Watt |
| Power Factor | >0.5 |
| Luminous Efficiency | 95 lumen/Watt |
| Energy Savings | 0,86 |
| Dimmable | No |
| Electrical Protection Class | Class II |

Mechanical Parameters

| | |
|--------------------------|--------------------------|
| IP Protection Class | IP20 |
| Switch On/Off Cycle | 30000 |
| Lifetime | 50000 hours |
| Body Material | Aluminum & PS & PET |
| Body Colour | White |
| Diffuser Material | PP |
| Reflector Material | PET/0.2mm |
| Cut-Hole Sizes | $\text{Ø}105$ millimeter |
| Product Height | $\text{Ø}119$ millimeter |
| Product Depth | 20 millimeter |
| Ambient Temperature (Ta) | -10°C<Ta<50°C |

Electrical Component Specifications

| | |
|------------------------|-----------------|
| Component Fitting Type | Internal Driver |
| Driver Properties | Isolated |
| Driver Input Voltage | 180-240 Volt |
| Driver Input Current | 0,027 Amper |
| Driver Output Voltage | 9-12 Volt |
| Driver Output Current | 0,028 Amper |

Logistic Informations

| | |
|---------------------|------------------------|
| Inbox Length | 145 millimeter |
| Inbox Width | 45 millimeter |
| Inbox Height | 125 millimeter |
| Outbox Length | 320 millimeter |
| Outbox Width | 310 millimeter |
| Outbox Height | 330 millimeter |
| Outbox Volume | 0,03274 m ³ |
| Outbox Quantity | 40 pieces |
| Unit Net Weight | 0,11 kilogram |
| Outbox Net Weight | 4,4 kilogram |
| Outbox Gross Weight | 6,2 kilogram |

IMPORTANT NOTES: VITO reserves the right to change/remove models or specifications partially/completely without any notice. Information, models and photographs of the products in this technical datasheet can not be used, reproduced or republished without permission. However, some parts can be quoted by giving reference and/or chapter number belonging to technical datasheet. Most of the items in the datasheet have been designed by our company within indicated technical specifications inside. Our company is not responsible for errors caused by wrong installation and operating against rules according to qualifications specified in the product details. Photographs printed in this datasheet may not reflect the actual color of the product depending on printing conditions. In the same context, typographical errors may possibly be found in the texts.