

Product Data Sheet

INDOOR LIGHTING

PROFILED SL1 32W

CODE: 2427230



Area of application

Surface-Mounted or Pendant-Mounted Linear LED lighting fixture to be installed on ceilings of corridors/rooms of homes, shopping malls, commercial areas, offices, schools, hospitals, industrial areas..

Product Advantages

PROFILED series LED LINEAR LIGHTING with Aluminum body and Polycarbonate Opal Diffuser with High Permeability presents 3360Lm lighting performance and 50000Hours long lifetime. This 32W model includes 4000K (NATURAL WHITE) LED for 120° light beam-angle as desired lighting flexibility. It's ready to be operated with its easy installation and maintenance. PROFILED SL1 series led linear fixtures are made by SAMSUNG chips and PHILIPS or TRIDONIC driver. There is option to be dimmable 220V, 0-10V, DALI, upon specific request.

Product Data Sheet

INDOOR LIGHTING

PROFILED SL1 32W

CODE: 2427230

Product Features

Electrical

Power (Watt): 32
Voltage: 220-240V AC ~ 50/60Hz
Power Factor: >0.9
Electrical Protection: Class I
Surge Protection: --
Dimmability: NO
Switch Cycle (Times): 30000

Material Characteristics

IP Class: IP20
IK Class: -
Material: Aluminum
Ambient Temperature: -20°C<ta<+40°C
Body Color: WHITE
Product Size (mm): 50x80x910

Technical Drawing




Lighting

Lumen (Lm): 3360
Luminaire efficacy (Lm/W): 105
Colour Temperature: 4000K (NATURAL WHITE)
Beam Angle: 120°
CRI: Ra >80
Lifetime (Hours): 50000
EEL : E

Packing Informations

Pieces/Outbox: 1
Outbox Size (mm): 70x1030x100
Outbox G.W. (Kg): 2,32
Outbox Volume (m³): 0,0072
Unit Weight (Gr): 2320
Barcode : 8698553617183

Light Distribution Curve



System Definition: PROFILED-SL/SUR/40K/WHT/32W/3360LM/5x8X91CM

VITO EUROPE

102 Iztochna Tangenta str. 4th Floor
P.C. 1528, Sofia/Bulgaria
Phone: +359 2 4341575
E-mail: info@vitoeurope.com

www.vitolighting.com