

Product Data Sheet

INDOOR LIGHTING

PROFILED SL1 42W

CODE: 2427350



Area of application

Surface-Mounted or Pendant-Mounted Linear LED lighting fixture to be installed on ceilings of corridors/rooms of homes, shopping malls, commercial areas, offices, schools, hospitals, industrial areas..

Product Advantages

PROFILED series LED LINEAR LIGHTING with Aluminum body and Polycarbonate Opal Diffuser with High Permeability presents 4410Lm lighting performance and 50000Hours long lifetime. This 42W model includes 4000K (NATURAL WHITE) LED for 120° light beam-angle as desired lighting flexibility. It's ready to be operated with its easy installation and maintenance. PROFILED SL1 series led linear fixtures are made by SAMSUNG chips and PHILIPS or TRIDONIC driver. There is option to be dimmable 220V, 0-10V, DALI, upon specific request.

Product Data Sheet

INDOOR LIGHTING

PROFILED SL1 42W

CODE: **2427350**

Product Features

Electrical

Power (Watt): 42
Voltage: 220-240V AC ~ 50/60Hz
Power Factor: >0.9
Electrical Protection: Class I
Surge Protection: --
Dimmability: NO
Switch Cycle (Times): 30000

Material Characteristics

IP Class: IP20
IK Class: -
Material: Aluminum
Ambient Temperature: -20°C<ta<+40°C
Body Color: WHITE
Product Size (mm): 50x80x1200

Technical Drawing




Lighting

Lumen (Lm): 4410
Luminaire efficacy (Lm/W): 105
Colour Temperature: 4000K (NATURAL WHITE)
Beam Angle: 120°
CRI: Ra >80
Lifetime (Hours): 50000
EEL : E

Packing Informations

Pieces/Outbox: 1
Outbox Size (mm): 70x1310x100
Outbox G.W. (Kg): 2,76
Outbox Volume (m³): 0,0092
Unit Weight (Gr): 2760
Barcode : 8698553617305

Light Distribution Curve



System Definition: PROFILED-SL/SUR/40K/WHT/42W/4410LM/5X8X120CM

VITO EUROPE

102 Iztochna Tangenta str. 4th Floor

P.C. 1528, Sofia/Bulgaria

Phone: +359 2 4341575

E-mail: info@vitoeurope.com

www.vitolighting.com