



# Napájacie zdroje LED



## KMC

ochrana proti skratu, preťaženiu, prepätiu, tepelná ochrana  
pracovná teplota: -20°C až +40°C

200-240 V

50/60 Hz

IP 20



KMC-15-12, obj. kód 30610015



KMC-20-12, obj. kód 30610020



KMC-30-12, obj. kód 30610030



KMC-50-12, obj. kód 30610050



KMC-60-12, obj. kód 30610060



KMC-75-12, obj. kód 30610075



KMC-100-12, obj. kód 30610100

obj. kód	typ	W	V	I	rozmer (mm)
30610015	KMC-15-12	15	12	1,25 A	103x35,5x16,5
30610020	KMC-20-12	20	12	1,66 A	103x35,5x16,5
30610030	KMC-30-12	30	12	2,5A	160x58x18
30610050	KMC-50-12	50	12	4,16A	160x58x18
30610060	KMC-60-12	60	12	5A	160x58x18
30610075	KMC-75-12	75	12	6,25A	160x58x18
30610100	KMC-100-12	100	12	8,33A	160x58x18



FTPC20V12-E, obj. kód 31610020  
FTPC20V24-E, obj. kód 31620020



FTPC30V12-C2, obj. kód 31610030  
FTPC30V24-C2, obj. kód 31620030



FTPC50V12-C2, obj. kód 31610050  
FTPC50V24-C2, obj. kód 31620050



FTPC75V12-C, obj. kód 31610075  
FTPC75V24-C, obj. kód 31620075



## FTPC-C

ochrana proti skratu, preťaženiu, prepätiu, pracovná teplota: -20- +45°C

180-264 V

47-63 Hz

IP 20



FTPC15V12-E, obj. kód 31610015



FTPC100V12-E, obj. kód 31610100  
FTPC100V24-E, obj. kód 31620100



FTPC150V12-E, obj. kód 31610150  
FTPC150V24-E, obj. kód 31620150

obj. kód	typ	W	V	I	rozmer (mm)
31610015	FTPC15V12-E	15	12	1,25 A	103x35,5x16,5
31610020	FTPC20V12-E	20	12	1,67 A	103x35,5x16,5
31610030	FTPC30V12-C2	30	12	2,5 A	154x50x14
31610050	FTPC50V12-C2	50	12	4.17 A	159,9x57,8x18
31610075	FTPC75V12-C	75	12	6,25 A	201x64x30
31610100	FTPC100V12-E	100	12	8,33 A	179,4x62,5x30,6
31610150	FTPC150V12-E	150	12	11 A	179,4x62,5x30,6
31620020	FTPC20V24-E	20	24	0,84 A	103 x 35,5 x 16,5
31620030	FTPC30V24-C2	30	24	1,25 A	154x50x14
31620050	FTPC50V24-C2	50	24	2,08 A	159,9x57,8x18
31620075	FTPC75V24-C	75	24	3,12 A	201x64x30
31620100	FTPC100V24-E	100	24	4,17 A	179,4x62,5x30,6
31620150	FTPC150V24-E	150	24	6,25 A	179,4x62,5x30,6