

TECHNICAL DATASHEET

LUZ-BC IP65 15W

04-07-2020



NO IMAGE
AVAILABLE

VT/LUZ-BC/15W/SMD/40K/19CM/IP65/220V/BULKHEAD

NOTES

General Informations

Stock Code	3400890
HSC/GTIP Code	9405.10.91.50.00
EAN-13 (Inbox Barcode)	6970233839330
ITF-14 (Outbox Barcode)	36970233839331

Electrical Characteristics

Current Type	AC
Operation Voltage	220-240 Volt
Operation Frequency	50/60 Hertz
Electrical Current	0,13 Amper
Power	15 Watt
Power Factor	>0.5
Luminous Efficiency	68 lumen/Watt
Energy Savings	0,85
Dimmable	No
Electrical Protection Class	Class II

Electrical Component Specifications

Component Fitting Type	Internal Driver
Driver Properties	DOB
Driver Input Voltage	220-240 Volt
Driver Input Current	0,13 Amper

Lighting Characteristics

Luminous Flux	1020 lumen
Time for 60% of Lumen	<0.5 seconds
Light Beam Angle	120°
Flicker	No
LED Type	SMD

Mechanical Parameters

IP Protection Class	IP65
Switch On/Off Cycle	30000
Lifetime	25000 hours
Body Material	ABS & PC
Body Colour	White
Diffuser Material	PC
Mounting Accessories	Screws
Product Height	45 millimeter
Product Width	Ø190 millimeter
Ambient Temperature (Ta)	-20°C<Ta<50°C

Logistic Informations

Outbox Length	400 millimeter
Outbox Width	310 millimeter
Outbox Height	400 millimeter
Outbox Volume	0,0496 m ³
Outbox Quantity	24 pieces
Unit Net Weight	0,288 kilogram
Outbox Net Weight	6,9 kilogram
Outbox Gross Weight	7,5 kilogram

IMPORTANT NOTES: VITO reserves the right to change/remove models or specifications partially/completely without any notice. Information, models and photographs of the products in this technical datasheet can not be used, reproduced or republished without permission. However, some parts can be quoted by giving reference and/or chapter number belonging to technical datasheet. Most of the items in the datasheet have been designed by our company within indicated technical specifications inside. Our company is not responsible for errors caused by wrong installation and operating against rules according to qualifications specified in the product details. Photographs printed in this datasheet may not reflect the actual color of the product depending on printing conditions. In the same context, typographical errors may possibly be found in the texts.