

# TECHNICAL DATASHEET

## LUZ-BS IP65 BLACK 15W

04-07-2020



VT/LUZ-BS/15W/SMD/40K/19CM//BLC/IP65/220V/BULKHEAD/

NOTES

### General Informations

Stock Code	3401020
HSC/GTIP Code	9405.10.91.50.00

### Electrical Characteristics

Current Type	AC
Operation Voltage	220-240 Volt
Operation Frequency	50/60 Hertz
Electrical Current	0,1 Amper
Power	15 Watt
Power Factor	>0.5
Luminous Efficiency	68 lumen/Watt
Energy Savings	0,85
Dimmable	No
Electrical Protection Class	Class II

### Electrical Component Specifications

Driver Properties	Internal DOB Driver
-------------------	---------------------

### Lighting Characteristics

Luminous Flux	720 lumen
Time for 60% of Lumen	<0.5 seconds
Light Beam Angle	120°
Flicker	No
LED Type	SMD

### Mechanical Parameters

IP Protection Class	IP65
Switch On/Off Cycle	25000x times
Lifetime	25000 hours
Body Material	ABS & PC
Body Colour	Black
Diffuser Material	PC
Mounting Accessories	Screws
Product Height	42 millimeter
Product Width	Ø190*190 millimeter
Ambient Temperature (Ta)	-20°C<Ta<50°C

### Logistic Informations

Outbox Length	405 millimeter
Outbox Width	325 millimeter
Outbox Height	405 millimeter
Outbox Volume	0,053 m <sup>3</sup>
Outbox Quantity	24 pieces
Unit Net Weight	0,365 kilogram
Outbox Net Weight	8,76 kilogram
Outbox Gross Weight	11,09 kilogram

IMPORTANT NOTES: VITO reserves the right to change/remove models or specifications partially/completely without any notice. Information, models and photographs of the products in this technical datasheet can not be used, reproduced or republished without permission. However, some parts can be quoted by giving reference and/or chapter number belonging to technical datasheet. Most of the items in the datasheet have been designed by our company within indicated technical specifications inside. Our company is not responsible for errors caused by wrong installation and operating against rules according to qualifications specified in the product details. Photographs printed in this datasheet may not reflect the actual color of the product depending on printing conditions. In the same context, typographical errors may possibly be found in the texts.